Behlman Power Products

COTS POWER SUPPLY

DCM1000(8)-6-(5,20)-(-5.2,12.5)-(-2,10)-(8.5,10.6)-8.5,3.5)-(15,16.7)-(-15,1.7)-(28,4.18) MODEL 00389-3

Behlman's 00389 COTS power supply is a highly reliable, switch mode units built for high-end industrial or Military applications. The 00389 can accept a three phase 115/200 VAC, 400 Hz input and can supply eight DC outputs. These rugged power supplies are built to support the rigor of airborne, shipboard and mobile applications, and designed to meet the input power requirements of MIL-STD-704 and RTCA-DO160. Unit is Base Plate cooled.

INPUT 115/200 VAC +/- 20%, 360-440 Hz. Input Transient protection per Mil-STD-704A

OUTPUT:

01.			
1.	+5 VDC @ 20 A		
2.	-5.2 VDC @ 12.5 A		
3.	-2 VDC @ 10 A		
4.	+8.5 VDC @ 10.6 A		
5.	-8.5 VDC @ 3.5 A		
6.	+15 VDC @ 16.7 A		
7.	-15 VDC @ 1.7 A		
8.	+28 VDC @ 4.18 A		
Load Regulation:	1.0% no load to full load at nominal line.		
Line Regulation:	0.1% for 10%-line change.		
PARD-Ripple & Noise: 1% of output voltage p-p maximum. (0.1-10 MHz bandwidth)			
Over voltage protection: 120% max.			
Short circuit protection: Output voltage drops to less than 1 volt,			
-	with automatic recovery		
Current Limit:	Output current limited to 130% of rated current (28V output is limited to 4.5A Max.)		
Efficiency:	75%.		

GENERAL CHARACTERISTICS- see O&C drawing 24015

Isolation

Input to Output: Input to Case:	1000 VDC 1000 VDC
Output to Case:	200 VDC
Dimensional Data:	12.00"L X 7.00"W X 2.38"H
Weight:	6.4 lbs
Input:	CBM5W5M0000S-759.0 POSITRONIC
Output:	CBM24W7F2000S-759.0 POSITRONIC

ENVIRONMENTAL:

Operating Temperature:-40°C to 80°C base plate cooledStorage Temperature:-57°C to 85°CMTBF125,000 @ 25 Degrees C base plate, Ground benign

Designed to meet the following MIL Standards		
Shock:	MIL-S-901; MIL-STD-810C	
Vibration:	MIL-STD-167; MIL-STD-810C; RTCA/DO-160	
Humidity:	MIL-STD-810C	
EMI/EMĆ:	MIL-STD-461C/D; RTCA/DO-160. RE102 with proper shielding.	

E in 🖓 🕒 🕇

ORBIT POWER GROUP Behlman Electronics Headquarters: 80 Cabot Court, Hauppauge, NY 11788 631 435-0410 800 874-6727 Fax: 631 951-4341

sales@behlman.com



www.behlman.com

00389-3_SS.04 April 14